

APPLICATIONS



Retail



Restroom



Healthcare



Outdoor environments

TECHNICAL SPECIFICATIONS

TECHNOLOGY / PERFORMANCE

Technology	Active infrared
number of IR sensors	2
Radio control type	Digital
Frequency	908 – 918 MHz (frequency hopping)
Emitted radio power	-25 dBm (transmitter)
Detection range	8" (20cm) max.
Battery life	3 years (at 150 activations per day)
Product temperature range	-22 – 158 °F (-30 – 70 °C)

ELECTRICAL

Power supply	3 VDC (2 AA batteries, each ~1.5 V max.)
Power consumption	< 0.5 mW (when idle) < 25 mW (upon RF transmission)

PHYSICAL

Dimensions (overall)

single gang	2 ¾" (W) × 4 ½" (H) × 1 ¼" (T)
double gang	4 ½" (W) × 4 ½" (H) × 1 ¼" (T)
round	6" (H/W) × 1 ¼" (T)
jamb	1 ¾" (W) × 4 ½" (H) × 1 ¼" (T)

Material Stainless steel 304 and PC

Weight
 Single gang: 0.34 lb
 Double gang: 0.55 lb
 Round: 0.71 lb
 Jamb: 0.29 lb

COMPLIANCE

IP rating	IP65
FCC certification	FCC: 2ABWS-10TD900PB IC: 4680A-10TD900PB

Every application is unique. To ensure you have what you need for yours, please consult your BEA Sales Representative.

RELATED PRODUCTS

10RD900	900 MHz receiver module
10TD900TR	900 MHz retrofit transmitter
10BR2-900	2-relay logic module

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

PRODUCT SERIES



10MS51W-S
single gang with "wave to open" text + hand logo, 900 MHz version




10MS51W-D
double gang with "wave to open" text + hand logo, 900 MHz version



10MS51W-R
round with "wave to open" text + hand logo, 900 MHz version



10MS51W-J
jamb with "wave to open" text + hand logo, 900 MHz version



10MS51W-SKIT
10MS51W-S sensors (2) + 10MSBOXSGSM boxes (2) + 10RD900 receiver



10MS51W-DKIT
10MS51W-D (2) sensors + 10MSBOXDGSM (2) boxes + 10RD900 receiver

ADDITIONAL OPTIONS

10MS51W-SA	single gang with "wave to open" text and accessibility logo, 900 MHz version
10MS51W-SP	single gang, plain, 900 MHz version
10MS51W-ST	single gang with "wave to open" text only, 900 MHz version
10MS51W-DA	double gang with "wave to open" text and accessibility logo, 900 MHz version
10MS51W-DP	double gang, plain, 900 MHz version
10MS51W-DT	double gang with "wave to open" text only, 900 MHz version
10MS51W-RA	6" round with "wave to open" text and accessibility logo, 900 MHz version
10MS51W-RP	6" round, plain, 900 MHz version
10MS51W-RT	6" round with "wave to open" text only, 900 MHz version
10MS51W-JA	jamb with "wave to open" text and accessibility logo, 900 MHz version
10MS51W-JP	jamb, plain, 900 MHz version
10MS51W-JT	jamb with "wave to open" text only, 900 MHz version


MOUNTING OPTIONS



10MSBOXSGSM
Box, MAGIC SWITCH, single gang, surface-mount



10MSBOXDGSM
Box, MAGIC SWITCH, double gang, surface-mount



10MSBOXRND6SM
Box, MAGIC SWITCH, 6" round, surface-mount



10MSBOXJAMB6SM
Box, MAGIC SWITCH, jamb, surface-mount

