



Models EXP-1, EXP-2, EXP-15, EXP-25

Explosion Proof Momentary Contacts

Models

EXP-1

N/O & N/C Momentary Switch,
CLASS I & II, Division I & II, GROUP
B, C, D, E, F & G, NEMA 7 & 8

EXP-15

Momentary Action Panic

EXP-2

N/O & N/C Latching Switch, CLASS
I & II, Division I & II, GROUP B, C,
D, E, F & G, NEMA 7 & 8

EXP-25

Latching Action Panic

Specifications

- Heavy cast NEMA type 7 enclosure
- Conforms to Class I, DIV. I and II, Group B, C, D, E, F and G
- One normally-open and normally-closed contact
- Contact rated 5A at 35 VDC or 120 VAC
- Pipe thread 1/2-14 NPT
- Size: 4" x 6-1/2" x 4-1/2"
- UL and ULC approved for hazardous locations

Features

- Designed for hazardous locations
- 2" push button silkscreened with black epoxy ink
- Latching action switch, labeled "PANIC"

Options

- Momentary action switch, labeled "PUSH TO EXIT"
- Latching action switch, labeled "PUSH TO EXIT"
- Momentary action switch, labeled "PANIC"
- Latching action switch, labeled "PANIC"
- Push button can be customized