

OVERHEAD INDUSTRIAL SENSOR COMPARISON





FALCON FAMILY

Motion sensor for industrial doors, gates & warning indication



IS40

Motion & presence sensor for industrial doors



LZR®-WIDESCAN

Motion, presence & safety sensor for industrial doors

SOLUTION COMPARISON

| | 10FALCON | 10IS40 | 10LZRWIDESCAN |
|----------------------|--|--|--|
| PRIMARY APPLICATIONS | | | |
| | Automatic Industrial Door Activation, Gate & Barrier Activation | Automatic Industrial Door Activation, Presence Detection | Automatic Industrial Door Activation, Pedestrian & Vehicle Presence Detection, Virtual Pull-Cord Activation, Cold Storage Environments, Dynamic Ground Conditions |
| TECHNICAL | | | |
| Technology | Microwave Doppler Radar | Microwave Doppler Radar / Active Infrared | LASER scanner, Time-of-Flight |
| Detection Mode | Motion | Motion / Presence | Motion & Presence (object direction, speed, size & height) |
| Max. Detection Zone | 13 × 16' @ 16' | Microwave: 13 x 16 ½' Infrared: 10 x 10' | Width: 1.2x Mounting Height Depth: 1.2x Mounting Height (adjustable depending on user settings) |
| FUNCTIONALITY | | | |
| Settings | Field size, Hold-Open Time, Output Configuration, Detection Mode, Detection Filter | Field Size (sensitivity), Hold-Open Time, Detection Mode, Detection Filter (rejection mode) | Teach-In; Presettings; Service Mode; Factory Reset; Red Spots; Out 1 Functions; Out 2 Functions; Relay Function; Motion (width, depth, object type, direction, immunity, door zone off, invert field); Presence (width, depth, object type, max. presence time, immunity, door zone off, invert field); Safety (width, depth, max presence, immunity, uncovered zone, invert field) |
| Features | Bidirectional, Unidirectional Approach and Unidirectional Depart | Bidirectional, Unidirectional Approach and Unidirectional Depart; 6 Modes of Pedestrian & Parallel Traffic Rejection | Background Independence, 3D Object Analysis, Full- and Partial Door Opening |