



- UL and cUL Listed, FM Approved, CSFM Listed, MEA Approved, ADA Compliant
- Single or dual action
- Terminal connectors
- 10 Amp snap action switch
- Gold plated SPST contacts
- Optional auxiliary contacts
- Mounts on standard single gang box
- Surface backboxes available
- Multiple colors and custom text available
- Glass break rod
- Made in the U.S.A.

Description

The Potter Special Application Pull Station Series offers a complete line of die-cast pull stations for a variety of applications with various colors and descriptions. The pull stations are available in single or dual action models, weather proof, explosion proof and multiple contact configurations. All of the pull stations have a 10-amp snap action switch and a dedicated terminal block for the ease of wire connections. All of the metal is completely coated to inhibit corrosion and provide for a uniform and quality finish.

The pull stations are available in red, blue, green, yellow, white, black, gray, purple or orange. The wording on the pull stations is customizable with a large variety of standardized units. The standard models have a hex key reset, however a key reset is also available. An institutional model is available that is operated with a key only. The models are available with shallow and deep surface mount back boxes.

The weather proof and explosion proof models include the appropriate back box with the pull station. The explosion proof is also inherently weather proof.

Operation

The Potter single action series of pull stations operate by pulling the white operating handle straight down and the handle will lock into place. The dual action stations require the lifting of the front cover and then pulling the white operating handle straight down. The stations are reset by opening the front and placing the handle in the normal position.

Engineering Specifications

The installer shall furnish and install the Potter Special Application Series of pull stations as indicated. The pull station shall be die cast construction with a "T" type pull handle that is ADA compliant. Single action pull stations shall be a RMS-1T. Dual action pull stations shall be the Potter RMS-1T-LP. Any units in an outdoor or wet location shall be an RMS-1T-WP. Explosion proof environments for Class 1 Groups B, C and D or Class 2 Groups E, F or G shall use the RMS-6T-EXP-WP. The contacts shall be a single pole, single throw switch rated at 1 amp 30 VDC/125 VAC. The device shall have a terminal block for ease of wiring. Once activated, the pull station shall be reset by opening the front cover. Opening of the cover in a normal state shall initiate an alarm.

Specifications

Switch Rating: 1 Amp @ 30 VDC
1 Amp @ 125 VAC
Pull Station Dimensions: 4 3/4" H x 3 1/4" W x 7/8" D

For fire alarm pull stations see bulletin #8900097.